




## FL Series-5




### Product Characteristic:


- High pressure die-casting aluminium housing and frame, treated by external electrostatic powder spraying, corrosion resistance. The frame fixed onto the body by stainless steel screws. The back side of the body adopts heat releasing slice design, prolong surface life;
- Sealing gasket: heatproof silicon sealing gasket surrounded the slots of whole housing providing high performance of protection against moisture and contaminant;
- Power: available for 42pcs, 56 pcs or 70 pcs individual LED, range 48~125W;
- Reflector: professional reflector design, could supply the accurate light distribution and high light efficiency;
- Surroundings Temperature Ta: -20°C~45°C;
- Installation Bracket: galvanized steel bracket, treated by external electrostatic powder spraying, corrosion resistance, fixed by stainless steel outer hexagonal screws at two sides, convenient for adjusting the projection angle; heavy-duty stainless steel bracket suitable for pendant mounted, wall mounted or ceiling mounted, optional for kids or projection angle adjustment.





15°



30°



45°



60°

Model	Power	Light Efficiency	Color Temperature	Light color
FLS-70- YS731	70W AC90- 277V	>100 lm/W	4000 K/ 5000 K/ 6000 K	Single white, yellow, red, green, RGB
FLS-100- YS731	95W AC90- 277V			
FLS-120- YS731	120 W AC90- 277V			